

AWES ROLLiant™ Hub Approved Lubricant Listing

This bulletin applies to all ROLLiant™ hub assemblies with the SKF X-Treme seal and provides a list of compatible lubricants. The lubricants have been tested and approved for compatibility with the SKF X-Treme seal. Accuride does not recommend or endorse any of these lubricants.

WARNING: The end user has the responsibility to ensure hub assemblies are filled with the correct amount of lubricant and are properly maintained. Refer to WES2.027 for hub installation instructions.

Lubricants meeting API GL-4 or GL-5 will typically be acceptable. **Please contact Accuride Engineering regarding approval of lubricants not on the list before use.**



Oil Lubricants

- Anglam OL 6055 75W-140
- BASF Emgard 2979 SAE 50 (75W-90) ¹
- BASF Emgard 2986 FE 75W-90 ²
- BASF Emgard 2989 L/S 75W-90 ³
- Castrol Syn GL 75W-90
- Chevron Delo Special
- Chevron Delo ESI 80W-90
- Chevron Delo ESI 80W-140
- Chevron RPM Synthetic 75W-90
- Chevron RPM Arctic 75W-90
- Chevron RPM 80W-90
- Cognis (2837) 75W-90 [EE] **
- Cognis (2837) Emgard EP 75W-90 [EE] **
- Cognis (2979) 75W-90 [EE] (rebranded as ¹)
- Cognis (2986) FE 75W-90 [EE] (rebranded as ²)
- Conoco 75W-140
- Emery Emgard L/S 75W-90 (rebranded as ³)
- Mobil HD Plus 85W-140
- Mobil Delvac 75W-140
- Mobil Delvac 75W-90

Oil Lubricants (Continued)

- Pennzoil 75W-90 GL5
- Shell Penzoil GO 80W-90
- Shell Spirax HD 80W-90
- Shell Spirax HD 80W-140
- Shell Spirax LL EW 80W-140
- Shell Alvania #3
- Texaco Multigear 85W140
- Texaco Syn-Star 80W-140
- Texaco Syn-Star 75W-90
- Texaco Syn-Torq GL5 75W-90

Grease Lubricants

Semi-fluid grease is only to be used in AWES approved trailer hub applications.

- Chevron Delo Synthetic Grease SF
- Chevron Delo Syn-Grease SFE EP
- Mobilith SHC 007

** Lubricant is discontinued